RECOMMENDED USE AND CARE FOR GARMENTS MADE WITH NOMEX® IIIA OR NOMEX® COMFORT FABRICS

DuPont[™] NOMEX[®] IIIA and NOMEX[®] COMFORT fabrics are composed of 93% DuPont[™] NOMEX[®] meta-aramid, 5% DuPont[™] KEVLAR[®] para-aramid and 2% carbon/nylon antistatic fiber.

Single layer garments made from these fabrics are not suitable for protection against continuous thermal loads, molten metal splash, hot liquids, or steam. Do not wear alone for structural or proximity fire fighting. Do not use for chemical protection. Follow all warning and use information included in garment manufacturer's labels.

Flammable contaminants will reduce the thermal protection of any flame resistant fabric and the garments made from them. Wash all garments made with NOMEX® IIIA or NOMEX® COMFORT fabric frequently to ensure that no greases, oily soils or other flammable contaminants are present when the garment is worn.

- Wash new garments before wearing to remove fabric processing aids and finishes.
- Launder garments separately from non-flame resistant clothing.
- Wash dark and light colors separately.
- Secure all closures before washing and drying
- Pretreat greasy stains.
- Machine wash in hot water (maximum 140 $^{\circ}F / 60 ^{\circ}C$) with a heavy duty detergent.
- Do not use chlorine bleach or detergents containing chlorine bleach.
- Tumble-dry on low heat (maximum 160 °F / 71 °C).
- Do not over-dry. Remove promptly.
- Do not use fabric softeners or dryer sheets.
- When using commercial laundry aids, be sure to read and carefully follow manufacturer's instructions.
- Removal of grease or oil stains may require dry cleaning.
- Do not store or line-dry fabrics or garments in sunlight.